

SYCALL RESET GLOW SINGLE POLE WEATHERPROOF RESETTABLE CALL POINTS

The Sycall Reset-Glow series of resettable manual call points mimics the feel of breaking glass whilst offering the user benefits and environmental advantages of a resettable operating element.

Internal and weatherproof units are available and all variants can be easily identified by an alarm flag which rises into view upon activation.

The optional in-built LED ring illuminates the central operating window of the Series 01 when operated.

FEATURES

- Clean contact or choice of 470 Ω or 680 Ω series resistors in the same model
- Aesthetically appealing design
- Approved to EN 54 Part 11 (Red Only)
- Resettable Element
- Optional highly visible LED Light ring when activated
- Luminescent element visible for up to 8 minutes

APPROVALS (Red Sycall Call Point Only)



PART NUMBERS

- SYW-RF01 Red, Series 01, Flush Mount
- SYW-GF01 Green, Series 01, Flush Mount
- SYW-YF01 Yellow, Series 01, Flush Mount
- SYW-WF01 White, Series 01, Flush Mount
- SYW-BF01 Blue, Series 01, Flush Mount
- SYW-RS01 Red, Series 01, Surface Mount
- SYW-GS01 Green, Series 01, Surface Mount
- SYW-YS01 Yellow, Series 01, Surface Mount
- SYW-WS01 White, Series 01, Surface Mount
- SYW-BS01 Blue, Series 01, Surface Mount

ACCESSORIES

- SYW-PC01 Sycall Hinged Protective Cover

SYCALL RESET GLOW



SPECIFICATION

| | |
|--------------------------------|--|
| Maximum Voltage | 30 V dc |
| Minimum Voltage* | 5.0 V dc if LED with R1 is chosen 6.0 V dc if LED if R2 is chosen |
| Current Rating (non activated) | 0 mA |
| Current Rating (activated) | 19 mA @ 12 V dc - R1 13 mA @ 12 V dc - R2 45 mA @ 24 V dc - R1 31 mA @ 24 V dc - R2 |
| Cable Termination | 0.5 2.5 mm ² |
| Operating Temperature | -30 to +70°C |
| IP Rating | IP67 |
| Material | ABS/Polycarbonate/PA6+Glass Fibre |

*LED may be low output or not operate below minimum voltage

SMART+GUARD 2

PROTECTIVE COVERS

- SG2-SS-# Smart+Guard 2 Cover, Surface, With Sounder
- SG2-S-# Smart+Guard 2 Cover, Surface No Sounder

For full product code replace # with:

R = Red
G = Green
Y = Yellow
W = White
B = Blue




SYCALL RESET GLOW

SINGLE POLE WEATHERPROOF


RESETTABLE CALL POINTS

INSTALLATION




Dimensions (mm)


Surface Mount (Front)



Side View



Surface Mount (Rear)



Terminal Layout

3700096_REV0201

We reserve the right to change or amend any design or specification in line with our policy of continuing development and improvement.

Vimpex LTD

Star Lane, Great Wakering,
Essex SS3 0PJ, UK
t. +44 (0) 1702 216999
e. sales@vimpex.co.uk
www.vimpex.co.uk

Vimpex Interguard AB

t. +46 (0) 36 37 10 65
e. sales@vimpex.se

