TECHNICAL DATASHEET

24 V N SERIES POWER SUPPLIES



The 24 V N range of power supplies has been designed for access control, CCTV, fire systems (where compliance with EN54-4 is not required) and general purpose applications. The products use energy efficient switch mode technology and have a universal mains supply input (90 - 264 V ac).

The modular range consists of 1, 2, 3 & 5 Amp power variants with full rated current to load and also feature a fully regulated output with low ripple and noise.

The products using switch mode technology are typically up to 87.5% efficient. This can save customers money by reducing energy bills and carbon footprint. Switch mode technology provides for lower power consumption, provides cool running and energy efficiency products that can result in improved long term reliability.

APPROVALS

CE 2831

FEATURES

- 27.6 V dc output
- Cost effective switch mode technology
- · Energy efficient reducing energy bills
- Modular construction means easy maintenance
 and upgrading
- Full rated current to load +0.8 Amp battery charging
- 90 264 V ac range
- Deep discharge protection
- Electronic overload protection
- Mains transient protection
- LED Indication:
 - Mains status
 - Output or battery fuse fail
 - Output short circuit or low voltage
 - Battery low or missing
- Screen printing available
- Three year warranty



PART NUMBERS

| Part No: | Description | Amp Rating | Battery Size | Size (mm) H X W X D |
|----------|--|---------------|----------------------------|---------------------|
| G2401N-A | Standard 27.6V dc 1.5A (1A to load + 0.5A battery charge) 2 x 1.2Ah | 1.0 | 2 x 1.2 Ah | |
| G2401N-C | Standard 27.6V dc 1.5A (1A to load + 0.5A battery charge) 2 x 7Ah | | 275 x 330 x 80 2 x 7 Ah | 275 x 330 x 80 |
| G2402N-C | Standard 27.6V dc 2.5A (2A to load + 0.5A battery charge) 2 x 7Ah | 2.0 | | |
| G2403N-C | Standard 27.6V dc 3.5A (3A to load + 0.5A battery charge) 2 x 7Ah | 3.0 | | |
| G2405N-C | Standard 27.6V dc 5.5A (5A to load + 0.5A battery charge) 2 x 7Ah | 5.0 | | |

SPECIFICATION

| Mains Input | 90 - 264 V ac at 50-60 Hz | | |
|-----------------------|---------------------------|--|--|
| Output | 27.6 V dc | | |
| Maximum Current | See table above | | |
| Operating Temperature | -10° to 40° at 95% RH | | |

3700145_REV0101

We reserve the right to change or amend any design or specification in line with our policy of continuing development and improvement.

Vimpex Ltd, Star Lane, Great Wakering, Essex SS3 OPJ, UK Vimpex Europe BV / Vimpex Sweden AB / Vimpex Fire & Security (Ireland) Ltd T: +44 (0) 1702 216999 / E: sales@vimpex.co.uk / W: vimpex.co.uk

