

LEJON KEMI

FFE Cleaner

FFE Cleaner is a cleaning agent specially developed for cleaning breathing apparatus (air cylinders, carrier slings, hoses, etc.) in PPE dishwashers and manually. The cleaner loosens and removes soot, oil and grease and other soiling from e.g. stainless steel, aluminium, glass, plastics, rubber and painted and lacquered surfaces. NB The product is not suitable for cleaning breathing masks in PPE dishwashers at higher temperatures than 50° C. With regard to breathing masks, the use of Lejon Kemi FPG Wash is recommended for washing in washing machines, provided the masks are enclosed in Lejon Kemi washing bags and Lejon Kemi's special washing program for breathing masks is used.

Dosage

PPE washing machines: approx. 1.0 % - (2 -3 % for heavily soiled equipment or for medium-hard – hard water).
Manual cleaning: 0.5-3 % (Heavily soiled surfaces: increase the dosage to up to 10 % or use concentrate).

Washing temperature

Dishwashers: 58° C - max. 60° C (both wash and rinse)

Recommended washing time

20-30 mins. excluding rinse.

Cleaning in PPE dishwashers

Always follow the breathing apparatus manufacturer's cleaning guidance and the dishwasher manufacturer's operating and maintenance instructions for the machine in question. Dosage, washing temperature and washing time should be set to the values given above. Heavily soiled equipment may require pretreatment with concentrated FFE Cleaner sprayed onto the equipment 2-3 minutes prior to washing in the machine and/or additional manual cleaning.

Manual cleaning

Spray on the recommended solution or dip the cleaning item in it. Allow the cleaner to act for 3-5 minutes. Rub the surfaces with a soft brush or sponge. Rinse off carefully with clean water. Hot water (40° C - 50° C) will increase the cleaning effect. **NB Do not allow the cleaner to dry in on the surfaces to be cleaned.**

Environmental information

Surfactants and complexing agents in the product are rapidly biodegradable. The packaging is made from polyethylene/polypropylene and can be recycled by sorting at source as hard plastic packaging.



Danger

Causes skin irritation. Causes severe eye damage

Wear protective gloves and safety glasses. Avoid inhaling vapour or spray. IN THE EVENT OF SKIN CONTACT: Wash with plenty of water. Remove contaminated clothing. IN THE EVENT OF CONTACT WITH EYES: Carefully flush with water for several minutes. Remove contact lenses if this can be done without difficulty. Continue flushing. Contact poisons information centre or a doctor.

Contains: Sodium silicates < 15 %, sodium 2-ethylhexyl sulphate <15 %.

Packaging

10 litre. Art. no.: 25 01000 01. 25 litre Art. no.: 25 0250 01

Protect from frost

2022-06-17I.L

Lejon Kemi AB – Developing environmentally friendly chem.-technical products
Fritz Janssons väg 20, SE-184 70 Åkersberga - Customer contact, Tel.: + 46 (0)76-827 00 96

E-mail: info@lejonkemi.se Website: www.lejonkemi.se